



Quickinfo

KT6564 @ 3000K, ≥ 80
10W, 30°, 700LM

Order options

Color temperature

2700K

3000K

4000K

Color rendering Index

≥ 80

≥ 90

LENS beam angle

KT6564-30°

KT6564A-30°

Control

Non dim

DALI

0~10V

Triac

RECESSED DOWNLIGHT



Light distribution

3000K CRI≥80

KT6564		Medium 30°
h (m)	E0° (lx)	Φ (m)
1	1076	0.54
2	268.9	1.07
3	119.5	1.61
4	67.2	2.15
5	43.1	2.69

Recessed wall washer downlight

Recessed wall washer downlight

Protection class IP 20


3 years availability guarantee

Family lights design is suitable for project selection. Three sizes with different powers can be met to your demand. Tilted front ring structure can be adjusted the lighting area arbitrarily.

The design of the luminaires may get upgraded and the specifications of them may be adjusted by different degree. Please visit our website and check the detail description and specification of the luminaires.

Finish color

For KT6565



LED		110-240V	IP20	Bridgelux	AREEK
-----	--	----------	------	-----------	-------

	W	LUM	CCT	BEAM	CRI	CUTOUT	W	L
KT6564	10	700	3000K	30°	80	78x78	82x82	79

