

XD2263 Ceiling Light



Zoomable Gimbal Waterproof





20°-50° The fixtures emit extremely precise light beams due to the excellent design.



Multiple waterproof processes but it doesn't affect the heat dissipation performance.





Quickinfo

XD2263 @ 3000K, ≥80 10W, [20-50°], 399-428LM

Order options

Color temperature				
2700K				
3000K				
4000K				

Color rendering index ≥80 ≥90

LENS beam angle XD2263-[20°-50°]

Control
Non dim
DALI
0~10V
Triac

CEILING LIGHT



IP65 Zoomer Ceiling Light

Symmetrical light distribution

Protection class IP65 3 years availability guarantee

Zoomable ceiling light with surface coating for outdoors suitable for public as well as private environment, such as entrances, eaves, carports, and also in sloping constructions. Outdoor lighting creates a welcoming impression and increases security around the property.

The design of the luminaires may get upgraded and the specifications of them may be adjusted by different degree. Please visit our website and check the detail description and specification of the luminaires.

LED [220-240V	IP6	5 Brid	dgelux	К	ìP			
	w	LUM	ССТ	BEAM	CRI	DIA1	DIA2	H1	H2	НЗ
XD2263	10	399-428	3000K	20-50°	80	Φ60	Φ100	150	31	213

Light distribution 3000K CRI≥80

XD2263	Medium 20°				
h (m)	E0° (lx)	Φ (m)			
1	3133	0.25			
2	783.3	0.50			
3	348.1	0.75			
4	195.8	1.00			
5	125.3	1.25			

	Wide 50°			
E0° (lx)	Φ (m)			
743.9	0.90			
168	1.80			
82.7	2.71			
46.5	3.61			
29.8	4.51			
	743.9 168 82.7 46.5			

Finish color

For XD2263





