



Multis Series - Magnetic Light



Control Type



Luminaire specifications

Mode	Power	Lumen	CCT	BA.	Light Source	Driver	CRI
MHTA8848	12W	1080	3000K	15/24/36/60°	Bridgelux	GLOBAL	90
MHTA8846	12W	1080	3000K	15/24/36/60°	Bridgelux	GLOBAL	90

All values are measured at 48V.
 Color temperature range 2700K/3000K/3500K/4000K/5000K/6000K/Tunable White.
 Colour Rendering Index (CRI) CRI80, CRI90
 Die-casting Aluminum

Frame Finishing color

- Black RAL9005
- Grey RAL9006
- White RAL9016



MHTA8848

Light distribution

3000K CRI 90

MHTA8848		47°
h (m)	E0° (lx)	Φ (m)
1	1010	0.88
2	252.5	1.76
3	112.2	2.64
4	63.1	3.52
5	40.4	4.40




MHTA8846


Light distribution

3000K CRI 90

MHTA8846		37°
h (m)	E0° (lx)	Φ (m)
1	2231	0.67
2	557.6	1.34
3	247.8	2.01
4	139.4	2.68
5	89.2	3.36



MHTA8848



MHTA8846

Remark: ● Technical information may change, please refer to the datasheet.