

# CUP SERIES



# Cup Series - Recessed Downlight



KT6913

### Light distribution

3000K CRI 90

KT6913		23°	
h (m)	E0° (lx)	Φ (m)	
1	1432	0.41	
2	358.1	0.82	
3	159.2	1.23	
4	89.5	1.63	
5	57.3	2.04	



KT6914

### Light distribution

3000K CRI 90

KT6914		24°	
h (m)	E0° (lx)	Φ (m)	
1	1243	0.42	
2	310.8	0.85	
3	138.2	1.27	
4	77.7	1.69	
5	49.7	2.12	



KT6943

### Light distribution

3000K CRI 90

KT6943		23°	
h (m)	E0° (lx)	Φ (m)	
1	1415	0.41	
2	353.8	0.82	
3	157.3	1.23	
4	88.5	1.64	
5	56.6	2.05	

### Control Type




### Luminaire specifications

Mode	Power	Lumen	CCT	BA.	Cutout	Light Source	Driver	CRI
KT6913	7W	600	3000K	15/25/38/60°	Φ80	EVER CORE	AREEK	90
KT6914	7W	600	3000K	15/25/38/60°	Φ80	EVER CORE	AREEK	90
KT6943	7W	600	3000K	15/25/38/60°	Φ83	EVER CORE	AREEK	90


All values are measured at 220V(+/- 10%).  
 Color temperature range 2700K/3000K/3500K/4000K/5000K/6000K/Tunable White.  
 Colour Rendering Index (CRI) CRI80, CRI90  
 Die-casting Aluminum

### Frame Finishing color


- Black RAL9005
- Grey RAL9006
- White RAL9016



KT6913



KT6914



KT6943

Remark: ● Technical information may change, please refer to the datasheet.