



EYE SERIES



Eye Series - Recessed Downlight



KT6826

Light distribution
3000K CRI 90

KT6826			44°
h (m)	E0° (lx)	Φ (m)	
1	1645	0.80	
2	411.2	1.60	
3	182.8	2.39	
4	102.8	3.19	
5	65.8	3.99	



KT6827

Light distribution
3000K CRI 90

KT6827			20°
h (m)	E0° (lx)	Φ (m)	
1	3182	0.35	
2	795.5	0.70	
3	353.5	1.05	
4	198.9	1.39	
5	127.3	1.74	

Control Type

- On-off
- 0-10V
- Phase-Cut
- DALI
- Casambi

Luminaire specifications

Mode	Power	Lumen	CCT	BA.	Cutout	Light Source	Driver	CRI
KT6826	16W	1100	3000K	15/25/38/60°	Φ165	Bridgelux	LIFUD	90
KT6827	16W	1050	3000K	15/25/38/60°	Φ100	Bridgelux	LIFUD	90

All values are measured at 220V(+/- 10%).
Color temperature range 2700K/3000K/3500K/4000K/5000K/6000K/Tunable White.
Colour Rendering Index (CRI) CRI80, CRI90
Die-casting Aluminum

Frame Finishing color

- Black RAL9005
- Grey RAL9006
- White RAL9016

