

NEW

# LESS G3



Next generation forging track spot -- Where Performance Meets Precision. Experience superior illumination with LESS G3 track light series, engineered for exceptional thermal management and visual comfort.



Available in customizable colors

Seamlessly blends functionality with aesthetics



Black  
RAL9005



Grey  
RAL9006



White  
RAL9016



Matt  
Silver



Golden  
Champagne



Rose  
Golden



Blue  
Peacock



DAG



Copper



## Heat Dissipation & Durability

Efficient heat dissipation  
thanks to forging structure with a lifespan  
up to 50,000 hours





3 sizes and powers application  
in commercial spaces

# LESS G3 - Recessed Downlight



## Light distribution

3000K CRI 90

MHT9023 12W		24°	
h (m)	E0° (lx)	Φ (m)	
1	5475	0.38	
2	1369	0.76	
3	608.3	1.14	
4	342.2	1.53	
5	219	1.91	



## Light distribution

2700K CRI 90

MHT9024 18W		24°	
h (m)	E0° (lx)	Φ (m)	
1	9548	0.41	
2	2387	0.82	
3	1061	1.23	
4	596.8	1.64	
5	381.9	2.05	



## Light distribution

2700K CRI 90

MHT9025 28W		24°	
h (m)	E0° (lx)	Φ (m)	
1	1566	0.38	
2	3915	0.77	
3	1740	1.15	
4	978.8	1.53	
5	626.4	1.92	

## Control Type on request

- On-off
- 0-10V
- Phase-Cut
- DALI
- Casambi



## Luminaire specifications

Model	Power	Lumen	CCT	BA.	Light Source	Driver	IP	CRI
MHT9023	12W	1100	3000K	24°	Bridgelux	KGP	20	90
MHT9024	18W	1885	3000K	24°	Bridgelux	KGP	20	90
MHT9025	28W	2892	3000K	24°	Bridgelux	KGP	20	90

## Frame finishing colour

Core Colours



## Colour temperature range



## Colour Rendering Index



## Front Reflector color



## Beam angle

MHT9023/9024/9025



